

Déclaration of performance

(according to regulation EU N°305/2011)

1) strip **S275J2** according EN 10025-2:2004

to be used in metallic structures

2)

NLMK La Louvière S.A.
2 rue des rivaux
B7100 La Louvière Belgique
Tel : +32(0)64 27.27.11 fax: +32(0) 27.28.48

CE marking notify body
OCAB/OCBS 1148
Boulevard de la plaine, 5 B 1050 Bruxelles
website: WWW,ocab-ocbs.com

system of assessment and verification of constancy of performance of the product according annex V:

Notified factory production control certification body N° 1148 performed :

-the initial inspection of the manufacturing plant and of factory production control
-the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control

Essential characteristic	performance	Harmonised technical specification
tolerances on dimensions and shape	dimension	EN 10051
	flatness	EN 10051
Yield strength	Nominal thickness (mm)	values Min (Mpa)
	>= <=	
	1,5 12,7	275
Tensile strength	Nominal thickness (mm)	values (Mpa)
	>= <=	Min Max
	1,5 2,99 3 12,7	430 580 410 560
elongation	Nominal thickness (mm)	values Min (Mpa)
	> <=	min (%) sample
	1,5 2 2,5 2,99 3 12,7	15 A80 16 A80 17 A80 21 A50
Impact strength	Nominal thickness (mm)	values Joules
	1,5 - 12,7 mm	27 J at - 20°C
Weldability CEV	Nominal thickness (mm)	values %
		max 0,40
Durability	Nominal thickness (mm)	values max %
	1,5 - 12,7 mm	C 0,18 Mn 1,5 P 0,025 S 0,025 Cu 0,55

EN 10025-1 :2004

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2.
signed for and on behalf the manufacturer by :

P Lesenfans
Quality & metallurgy dpt

16th November 2015

